



C2354E HYPERCELL

HPL 4.3-10 male connector

GENERAL CHARACTERISTICS

Inner Conductor:	Silver - plated bronze
Dielectric:	PTFE
Body:	Copper alloy - plated brass
Clamping and Coupling Nut:	Nickel - plated brass
Clamping Nut Waterproof:	Silicone O-ring
Coupling Waterproof:	Silicone O-ring

MECHANICAL & ENVIRONMENTAL

Interface Durability:	>100 cycles	
Temperature:	Operating	-40°C / +85°C
	Installation	-25°C / +55°C
	Storage	-50°C / +85°C
Weight:	96.2 g	
Waterproof Index:	IP68	
RoHS Compliance:	Yes	

ELECTRICAL

Impedance:	$50 \pm 1 \Omega$
Operating Frequency Band:	DC ~ 4GHz
VSWR:	DC ~ 3 GHz: ≤ 1.10
	3 ~ 4 GHz: ≤ 1.20
3rd Order Passive Intermodulation, Measured In Swept Frequency Mode with 2 20W carriers, $F \leq 1880$ MHz:	≤ -160 dBc
Voltage Test (at sea level):	2000 V eff / 50 Hz
Operating Voltage (at sea level):	1300 V eff / 50 Hz
Insulation Resistance:	$\geq 5000 M\Omega$
Contact Resistance:	Inner contact: $\leq 1.0 m\Omega$
	Outer contact: $\leq 1.0 m\Omega$

RANGE

Compatibility with ACOME HPL 50 -1/2F

M1473, M2831, M5445,M5454,M5453, M5398,M5644,M5646

Test Methods: IEC 61169-54, IEC 62037-3, IEC 60529

RECOMMENDATIONS

INSTALLATION INSTRUCTION

ANM - C2354E