



C6005E-500 HYPERCELL

Jumper 3/8SF PE 7/16 Din Male - N Male Elbow

GENERAL CHARACTERISTICS

Cable:	ACOME 50-3/8SF PE cable
Connector:	7/16 Din male / N male elbow
Assembly:	Inner and outer contact 100% soldered and with thermal shrink tube

MECHANICAL & ENVIRONMENTAL

Material and Finish of Connector Body:		Copper alloy - plated brass
Material and Finish of Coupling Nut:		Nickel - plated brass
Material and Finish of Inner Conductor:		Silver - plated bronze
Coupling Waterproof:		Silicone Rubber O-ring
Coupling Torque:	N interface	2.5 N.m Max.
	Din interface	30 N.m Max.
Minimum Bending Radius:		25 mm

ENVIRONMENTAL

Operating Temperature Range:	$-55^{\circ}\text{C} < \theta < +70^{\circ}\text{C}$
Waterproof Index:	IP68 (1m /24 h)
RoHS Compliance:	Yes
Test Methods:	IEC 61169, IEC 60529

ELECTRICAL

Impedance:		50 ± 1Ω			
Operating Frequency Range:		DC ~ 3GHz			
RMS Power (40 °C - 2 GHz):		0.51 KW			
Velocity:		83%			
Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carries:	IM3 at 900MHz	≤ -145 dBc			
	IM3 at 1800MHz	≤ -145 dBc		IM7 at 2100MHz	≤ -145 dBc

RANGE

Length (m)	Product number	Weight (g)	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
			RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
2	C6005E-L200	420	-28	0.39	-26	0.59	-24	0.70
4	C6005E-L400	675	-28	0.67	-26	1.01	-24	1.20
5	C6005E-500	800	-28	0.81	-26	1.22	-24	1.45