



## C1316X HYPERCELL

Jumper 1/2SF LSOH N Male - N Female

## GENERAL CHARACTERISTICS

|            |                                                        |
|------------|--------------------------------------------------------|
| Cable:     | ACOME 50-1/2SF LSOH cable                              |
| Connector: | N male / N female                                      |
| Assembly:  | Inner and outer contact 100% soldered and with molding |

## MECHANICAL & ENVIRONMENTAL

|                                         |                             |
|-----------------------------------------|-----------------------------|
| Material and Finish of Connector Body:  | Copper alloy - plated brass |
| Material and Finish of Coupling Nut:    | Nickel - plated brass       |
| Material and Finish of Inner Conductor: | Silver - plated bronze      |
| Coupling Waterproof:                    | Silicone Rubber O-ring      |
| Coupling Torque:                        | 2.5 N.m Max.                |
| Minimum Bending Radius:                 | 25 mm                       |

## ENVIRONMENTAL

|                              |                                                      |
|------------------------------|------------------------------------------------------|
| Operating Temperature Range: | $-40^{\circ}\text{C} < \theta < +70^{\circ}\text{C}$ |
| Waterproof Index:            | IP68 (1m /24 h)                                      |
| RoHS Compliance:             | Yes                                                  |
| Test Methods:                | IEC 61169, IEC 60529                                 |

ELECTRICAL

|                                                                               |                |            |  |                |            |
|-------------------------------------------------------------------------------|----------------|------------|--|----------------|------------|
| Impedance:                                                                    |                | 50 ± 1Ω    |  |                |            |
| Operating Frequency Range:                                                    |                | DC ~ 3GHz  |  |                |            |
| RMS Power (40 °C - 2 GHz):                                                    |                | 0.52 KW    |  |                |            |
| Velocity:                                                                     |                | 83%        |  |                |            |
| Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carries: | IM3 at 900MHz  | ≤ -160 dBc |  |                |            |
|                                                                               | IM3 at 1800MHz | ≤ -160 dBc |  | IM7 at 2100MHz | ≤ -160 dBc |

RANGE

| Length (m) | Product number | Weight (g) | Frequency 0/1000MHz |          | Frequency 1000/2200MHz |          | Frequency 2200/3000MHz |          |
|------------|----------------|------------|---------------------|----------|------------------------|----------|------------------------|----------|
|            |                |            | RL (dB)             | ATT (dB) | RL (dB)                | ATT (dB) | RL (dB)                | ATT (dB) |
| 1          | C1316X         | 310        | -32                 | 0.21     | -30                    | 0.33     | -26                    | 0.38     |
| 2          | C1309X         | 500        | -32                 | 0.33     | -30                    | 0.49     | -26                    | 0.59     |
| 3          | C1310X         | 690        | -32                 | 0.43     | -30                    | 0.66     | -26                    | 0.79     |