



C2285E-L200 HYPERCELL

Jumper 1/2SF LSOH 4.3-10 Male – 7/16 Din Male

GENERAL CHARACTERISTICS

Cable:	ACOME 50-1/2SF LSOH cable
Connector:	Screw Type 4.3-10 Male /7/16 Din Male
Assembly:	Inner and outer contact 100% soldered and with molding

MECHANICAL & ENVIRONMENTAL

Material and Finish of Connector Body:		Copper alloy - plated brass
Material and Finish of Coupling Nut:		Nickel - plated brass
Material and Finish of Inner Conductor:		Silver - plated bronze
Coupling Waterproof:		Silicone Rubber O-ring
Coupling Torque:	Din interface	30 N.m Max.
	4.3-10 interface	8 N.m Max
Minimum Bending Radius:		25 mm

ENVIRONMENTAL

Operating Temperature Range:	$-40^{\circ}\text{C} < \theta < + 70^{\circ}\text{C}$
Waterproof Index:	IP68 (1m /24 h)
RoHS Compliance:	Yes
Test Methods:	IEC 61169, IEC 62037, IEC 60529

ELECTRICAL

Impedance:		50 ± 1Ω			
Operating Frequency Range:		DC ~ 3GHz			
RMS Power (40 °C - 2 GHz):		0.50 KW			
Velocity:		83%			
Passive Intermodulation Measured In Swept Frequency Mode, With 2X20W Carries:	IM3 at 900MHz	≤ -161 dBc			
	IM3 at 1800MHz	≤ -161 dBc		IM7 at 2100MHz	≤ -161 dBc

RANGE

Length (m)	Product number	Weight (g)	Frequency 0/1000MHz		Frequency 1000/2200MHz		Frequency 2200/3000MHz	
			RL (dB)	ATT (dB)	RL (dB)	ATT (dB)	RL (dB)	ATT (dB)
1	C2285X-L100	320	-32	0.31	-30	0.37	-26	0.41
2	C2285X-L200	505	-32	0.42	-30	0.54	-26	0.60
3	C2285X-L300	695	-32	0.53	-30	0.71	-26	0.81
4	C2285X-L400	885	-32	0.64	-30	0.87	-26	1.05
5	C2285X-L500	1070	-32	0.75	-30	1.05	-26	1.20