



## C0270F HYPERCELL

HPL Framework Grounding Kit

### GENERAL CHARACTERISTICS

|                  |                                                                  |
|------------------|------------------------------------------------------------------|
| Framework Body:  | EPDM + Stainless steel                                           |
| Grounding Cable: | Copper (0.6m length)                                             |
| Compatibility:   | Matching with the cable with copper or Aluminium outer conductor |

### MECHANICAL & ENVIRONMENTAL

|                   |       |
|-------------------|-------|
| Color:            | Black |
| Waterproof Index: | IP68  |
| RoHS Compliance:  | Yes   |

### ELECTRICAL

|                            |                                                                                |
|----------------------------|--------------------------------------------------------------------------------|
| Impact Current Resistance: | Grounding kit is able to bear or endure concussion current level reaching 70KA |
| Contact Resistance:        | $\leq 5 \text{ m}\Omega$                                                       |

# RANGE

| Product number | Type                 | Approx. weight (g / p) |
|----------------|----------------------|------------------------|
| C0275F         | 1/4XF (φ6.85 × 600)  | 190                    |
| C1113F         | 1/4F (φ6.85 × 600)   | 190                    |
| C0270F         | 3/8XF (φ10.1 × 600)  | 190                    |
| C1114F         | 3/8F (φ10.1 × 600)   | 190                    |
| C0271F         | 1/2F (φ16 × 600)     | 200                    |
| C0272F         | 7/8F (φ27 × 600)     | 215                    |
| C0273F         | 1-1/4F (φ39.5 × 600) | 245                    |
| C0274F         | 1-5/8F (φ50 × 600)   | 255                    |